

Description

FiberPlex VCB breakout cables provide an easy solution for connecting to LightViper products.

The VCB analog cables conform to the industry standard Tascam DA-88 analog pinout convention. They can be order with Male or Female XLR connectors or TRS balanced 1/4" plugs.

The cables are hand assembled in the US using top quality cable and components. Professional quality Neutrik XLR and 1/4" plugs are coupled with pro grade DB25 connectors. The cable is Gepco X-Band XB408, 24AWG stranded oxygen free copper conductors, 8 twisted pair cable. Pairs are individually shielded (95% braid) , jacketed and color coded for easy and fast identification and bundled under one jacket making leads easy to trace and easy to change.



Analog Cables

Features:

- High quality copper breakout cables
- Standardized pinout
- Quality Neutrik connectors

Specifications

Cable	First End	Second End	Conductors	Cable	Insulation	Jacket
VCB-ADXM-15	DB25	XLRM	8	24 AWG Stranded Oxygen-free BC	Foam Polypropylene	Ultra-flex-ible G-Flex PVC
VCB-ADXF-15		XLRF				
VCB-ADTS-15		TRS				

Ordering Info

VCB-ADXM-15 - Breakout cable, DB25 to (8) XLR male, 15'

VCB-ADXF-15 - Breakout cable, DB25 to (8) XLR female, 15'

VCB-ADTS-15 - Breakout cable, DB25 to (8) TRS 1/4", 15'