

Description

FiberPlex VCB breakout cables provide an easy solution for connecting to LightViper products.

Our VCB handcrafted 110-ohm digital audio snakes are perfect for multiple channel transmission of 110-ohm AES/EBU digital audio data, and come in both 16 channel and 32 channel configurations (2 audio channels per conductor pair per AES3).

There are several configurations designed to interface a LightViper system with ProTools, Yamaha, Aphex or other equipment.

Made with Gepco's thin profile flexible precision DS6 series digital snake cable, professional quality DB25 connectors, our digital snakes are ideal for multichannel AES breakouts from AD/DA converters, digital mixers, or digital multi-track recorders. Gepco DS6 series is characterized up to 25MHz for 192kHz transmission. Pairs are precision twisted with a non-conductive polyethylene filler rod, shielded, and isolated with color-coded pair jackets. Gepco's cable construction techniques lower attenuation, minimize crosstalk, and stabilizes the impedance, reducing cable induced bit-errors and jitter.



Special Cables

Features:

- High quality copper breakout cables
- Interface Third Party gear with LightViper

Specifications

Conductor	26AWG
Impedance	110 Ω
Capacitance	14 pF/ft between conductors
Bandwidth	25MHz
Pair Shield	100% Foil
Dielectric	Foam Polypropylene
8 Pair Outer Diameter	.560in (14.2mm)
4 Pair Outer Diameter	.435in (11.1 mm)

Ordering Info

VCB-DDMY-10

Cable, Digital, 8 Channel AES3, 1 D-25M to 2 D-25, Y Card Input Only Compatible, 10'

VCB-DDMYIO-10

Cable, Digital, 16 Channel AES3, 2 D-25M to 2 D-25, Y Card I/O Compatible, 10'

VCB-DDAD8HR-10

Cable, Digital, 8 Channel AES3, 1 D-25M to 2 D-25, AD8HR Output Only Compatible, 10'

VCB-DDPT-10

Cable, Digital, 8 Channel AES3, 1 D-25M to 2 D-25, Pro Tools Input Only Compatible, 10'

VCB-DDPTIO-10

Cable, Digital, 16 Channel AES3, 2 D-25M to 2 D-25, Pro Tools I/O Compatible, 10'

VCB-DDA4-10

Cable, Digital, 4 Channel AES3, 1 D-25M to 1 D-15, Aphex Pinout, 10'

VCB-DDA8-10

Cable, Digital, 8 Channel AES3, 1 D-25M to 2 D-15, Aphex Pinout, 10'

